



We confirm the shape of the rail and the on the drawing mentioned distances. Dimensions from the staircase were taken from drawings we supplied. Therefore Lifts4U POLAND is unable to accept responsibility should any problems arise as a result of differences in measurements on site preventing installation of the lift.

Date, Signature \_\_\_\_\_

COLOR: RAL 7035

OMEGA-F - ELECTRIC CONNECTION

EL supply 230V AC 50Hz (cable 3C×2.5), length of free end of electric 2m, together with cable earth connecting Cr6mm, green/yellow ensure customer before installation of platform.  
 EI supply must be attach individual electric circuit breaker 16A/C and residual current circuit breaker (RCCB) for residual sinusoidal alternating currents 0.03A, type A-G, sensitive residual pulsating direct currents

Order: Wolow\_Glycz

POWER SUPPLY (EL-CONTROL BOX) 1x230V EI-MOTOR: 1.1kW/3x230V nmot=1400 1/min  
 GEAR BOX TYPE: SRS50/71B14 21-30, 2°-1°/0

ROPE DIA (mm)	ROPE LENGTH (mm)	ROPE WEIGHT (kg)	ROPE DIA (mm)	ROPE LENGTH (mm)	ROPE WEIGHT (kg)
13 (1)	1565	0.8	15 (1)	1565	0.8
13 (1)	1565	0.8	15 (1)	1565	0.8
13 (1)	1565	0.8	15 (1)	1565	0.8
13 (1)	1565	0.8	15 (1)	1565	0.8
13 (1)	1565	0.8	15 (1)	1565	0.8

PIVOT	LENGTH
A	800
B	800
C	1595
D	1600
E	1610
F	1600
G	1500
H	1530

DISTANCE RING	LENGTH
A	800
B	800
C	1595
D	1600
E	1610
F	1600
G	1500
H	1530

INDEX Datum Jmno Zmno

Datum: Jmno Matriko: Objedinjet: Lifts4U Konrad Jurek  
 Krsnik 74.116 Dostak 1:20 Ulica 87  
 Schwilli 48-202 Czestochowa POLAND

SP OMEGA-F

SP 5185

BEKOR 479, 687 64 Tel.: 072 646 234  
 Podzolul 44448 01 Dobre Szosy 44  
 Tel.: 072 480 615 Fax: 072 480 600  
 www.lifts4u.pl  
 lifts4u@lifts4u.com  
 lifts4u.de@lifts4u.com